

Kodumasinade ventilaatorid

TD - Mixvent



TD Silent



| Tüüp | Võimsus (kW) | Pinge (V) | Vool (A) | Pöörete arv (x/min) | Õhukogus (m ³ /h) | Surve max Pa | Kaal (kg) | Mürategur (dB) | Töötemperatuur (C) | IP kaitseaste |
|-------------------------------------|--------------|------------|----------|---------------------|------------------------------|--------------|-----------|----------------|--------------------|---------------|
| TD-160/100 N Silent | 0.02 | 230V, 50Hz | 0.16 | 2500 | 180 | 90 | 1.4 | 24 | -20 +40 | IP 44 |
| TD-2000/315 SILENT | 0.297 | 230V, 50Hz | 1.28 | 2680 | 1770 | 700 | 25 | 39 | -20 +60 | IP 44 |
| TD-2000/315 SILENT | 0.191 | 230V, 50Hz | 0.79 | 2300 | 1500 | 480 | 25 | 33 | -20 +60 | IP 44 |
| TD-1300/250 SILENT | 0.197 | 230V, 50Hz | 0.83 | 2570 | 1270 | 525 | 20 | 35 | -20 +60 | IP 44 |
| TD-1300/250 SILENT | 0.145 | 230V, 50Hz | 0.61 | 2190 | 1070 | 460 | 20 | 31 | -20 +60 | IP 44 |
| TD-1000/200 Silent | 0.12 | 230V, 50Hz | 0.5 | 2500 | 1100 | 300 | 8.7 | 21 | -20 +60 | IP 44 |
| TD-1000/200 Silent | 0.1 | 230V, 50Hz | 0.45 | 2000 | 800 | 270 | 8.7 | 20 | -20 +60 | IP 44 |

| | | | | | | | | | | |
|--|-------|---------------|------|------|-----|-----|------|----|---------|-------|
| <u>TD-800/200 Silent</u> | 0.095 | 230V, 50Hz | 0.45 | 2780 | 880 | 260 | 8.7 | 19 | -20 +60 | IP 44 |
| <u>TD-800/200 Silent</u> | 0.09 | 230V, 50Hz | 0.43 | 2480 | 700 | 245 | 8.7 | 18 | -20 +60 | IP 44 |
| <u>TD-500/150-160 Silent</u> | 0.05 | 230V, 50Hz | 0.22 | 2500 | 580 | 275 | 6 | 22 | -20 +60 | IP 44 |
| <u>TD-500/150-160 Silent</u> | 0.044 | 230V, 50Hz | 0.19 | 1950 | 430 | 225 | 6 | 17 | -20 +60 | IP 44 |
| <u>TD-350/125 Silent</u> | 0.03 | 230V, 50Hz | 0.13 | 2250 | 380 | 140 | 4.94 | 20 | -20 +40 | IP 44 |
| <u>TD-350/125 Silent</u> | 0.022 | 230V, 50Hz | 0.1 | 1900 | 280 | 115 | 4.94 | 19 | -20 +40 | IP 44 |
| <u>TD-250/100 Silent</u> | 0.024 | 230V, 50Hz | 0.11 | 2200 | 240 | 140 | 5.4 | 24 | -20 +40 | IP 44 |
| <u>TD-250/100 Silent</u> | 0.018 | 230V, 50Hz | 0.1 | 1850 | 180 | 115 | 5.4 | 19 | -20 +40 | IP 44 |
| <u>TD-160/100 N Silent</u> | 0.025 | 230V, 50Hz | 0.16 | 2500 | 180 | 102 | 1.4 | 24 | -20 +40 | IP 44 |
| <u>TD-160/100 N Silent</u> | 0.012 | 230V, 50Hz | 0.1 | 2200 | 140 | 85 | 1.4 | 21 | -20 +40 | IP 44 |