

Kodumasinade ventilaatorid

TD - Mixvent



TD Silent



Tüüp	Võimsus (kW)	Pinge (V)	Vool (A)	Pöörete arv (x/min)	Õhukogus (m ³ /h)	Surve max Pa	Kaal (kg)	Mürategur (dB)	Töötemperatuur (C)	IP kaitseaste
TD-160/100 N Silent	0.02	230V, 50Hz	0.16	2500	180	90	1.4	24	-20 +40	IP 44
TD-2000/315 SILENT	0.297	230V, 50Hz	1.28	2680	1770	700	25	39	-20 +60	IP 44
TD-2000/315 SILENT	0.191	230V, 50Hz	0.79	2300	1500	480	25	33	-20 +60	IP 44
TD-1300/250 SILENT	0.197	230V, 50Hz	0.83	2570	1270	525	20	35	-20 +60	IP 44
TD-1300/250 SILENT	0.145	230V, 50Hz	0.61	2190	1070	460	20	31	-20 +60	IP 44
TD-1000/200 Silent	0.12	230V, 50Hz	0.5	2500	1100	300	8.7	21	-20 +60	IP 44
TD-1000/200 Silent	0.1	230V, 50Hz	0.45	2000	800	270	8.7	20	-20 +60	IP 44

<u>TD-800/200 Silent</u>	0.095	230V, 50Hz	0.45	2780	880	260	8.7	19	-20 +60	IP 44
<u>TD-800/200 Silent</u>	0.09	230V, 50Hz	0.43	2480	700	245	8.7	18	-20 +60	IP 44
<u>TD-500/150-160 Silent</u>	0.05	230V, 50Hz	0.22	2500	580	275	6	22	-20 +60	IP 44
<u>TD-500/150-160 Silent</u>	0.044	230V, 50Hz	0.19	1950	430	225	6	17	-20 +60	IP 44
<u>TD-350/125 Silent</u>	0.03	230V, 50Hz	0.13	2250	380	140	4.94	20	-20 +40	IP 44
<u>TD-350/125 Silent</u>	0.022	230V, 50Hz	0.1	1900	280	115	4.94	19	-20 +40	IP 44
<u>TD-250/100 Silent</u>	0.024	230V, 50Hz	0.11	2200	240	140	5.4	24	-20 +40	IP 44
<u>TD-250/100 Silent</u>	0.018	230V, 50Hz	0.1	1850	180	115	5.4	19	-20 +40	IP 44
<u>TD-160/100 N Silent</u>	0.025	230V, 50Hz	0.16	2500	180	102	1.4	24	-20 +40	IP 44
<u>TD-160/100 N Silent</u>	0.012	230V, 50Hz	0.1	2200	140	85	1.4	21	-20 +40	IP 44